			Л		I		3	+	7	2		1		1			
	THE INEC	RMATION		WING IS THE	PROERTY OF CE	I ESTRA IS	3	V	CELESTRA		SIZE	I BOLT	В	C		D	
	DISCLOS	ED IN CON	FIDENCE AND FOR WHICH	D NOT TO BE	REPRODUCED, U	SED OR			CAT.NO	CODE	FLEX	SIZE	MIN	-	⊓ ±0.01	±0.015	
	DISLOSE	JEAGEPT		FORMISHED.]		DA4056A	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	5/16	0.87	1.03	0.56	0.14	
D	NOT	E:	SPE 2. ALL	CIFIED. DA,DB,LA,L	NS ARE IN INCH B,WP AND J SI DERWRITERS	ERIES OF CA	T.NO.S ARE		<u>D</u>								D
	мат	ERIAL:	ON O PRE OTH WITI	CODE WIRE -FIX CAT.N IERWISE SF H "P".	ES AND FLEX/2 O.WITH "L" HAS PECIFIED IN TH	4 STRANDED S NOT PEEP IE SUFFIX OF	D CABLES. HOLE UNLESS F THE CAT.NO.		B								
С										Beveled wire entry							
\rightarrow	INSTALLATION GUIDE DIE CODE = 54 DIE COLOR = Purple								Wire inspection hole								\leftarrow
В	B COULSED LISTED WIRE CONNECTORS ZAVV/27/8 ES13913									OLT SIZE	Color coded barr	el mar	kings -				В
																	—
										HUYA® CELESTRA CORPORATION www.huyaco.com 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.							
A									Image: Wire connectors and soldering A LUGS FOR CODE AND FLEX CABLE A								
	00 23	-Aug-25	Ruby Feng	Sinia Qiu	Cel	estra Standar	ds Spec. Initialed.		MA	ATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	PRT. NO. DA4056A		CALE NT	s	ID ANGLE PR		
T	REV	DATE	DWN	СНК		DESCRI	PTION		ECN FIN	ELECTRO TIN PLATE	DWG. NO. 186-cp17	12 U	NIT IN	сн] Ч	Ф-E		,
	_	_	4				3	4	7	2			_	1	_	_	