	4		3	\downarrow		2		1					
Ι	DISCLOSED IN CON		THE PROERTY OF CELESTRA BE REPRODUCED, USED OR			LESTRA AT.NO	WIRE CODE	SIZE FLEX	BOLT SIZE	B MIN ±	~	H D 0.01 ±0.01	5
					DA4	034A-260	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	3/4	1.52 1	1.05 0	.56 0.13	
D	NOTE:	SPECIFIED.	SIONS ARE IN INCHES UN										D
		LISTED BY	A,LB,WP AND J SERIES UNDERWRITERS INC." A IRES AND FLEX/24 STRA										
			T.NO.WITH "L" HAS NOT E SPECIFIED IN THE SUF		B B								
С	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE								30.				с
C	SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry												
\rightarrow	INSTALLATION GUIDE DIE CODE = 54 DIE COLOR = Purple					Wire inspection hole							
В	B CONNECTORS								el mark	ings —			В
													—
							HUYA ww.huyaco.cor		ncun R	d. Zhor	ngcun	Town.	
A					LUGS FOR CODE AND FLEX CABLE							A	
	00 23-Aug-25 REV DATE	Ruby FengSinia (DWNCH		tandards Spec. Initialed.		CN FINISH	RIAL HIGH-CONDUCTIVITY WROUGHT COPPER	PRT. NO. DA4034A-260 DWG. NO. 186 cp17	SCA UNI	NTS	$- \square$		N
	REV DATE	4		3			ELECTRO TIN PLATE	186-cp172	23	' INCH	1		J