								- 1									
			4				3	$\triangle$	7	2				1			
ı					ROERTY OF CELESTRA				CELESTRA	`	SIZE	BOLT	В	С	Н	D	] '
		SED EXCEPT			EPRODUCED, USED OR				CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.01	±0.015	
									DA4034A-25	51 4/0 AWG	550/24 = 222 kcmil 4/0 Weld	3/4	1.52	1.19	0.65	0.16	
											-				1	ı	1
D																	D
	N	OTE:		DIMENSIONS	S ARE IN INCHES UN	ILESS OTH	HERWISE										
			2. Al I	DA.DB.I A.I B	.WP.AL.AS AND J.SF	FRIES OF (	CAT.NO.S ARE				ı	1	D	-			
		2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE															
	ON CODE WIRES AND FLEX/24 STRANDED CABLES.										<i>A</i> A				l —		
					WITH "L" HAS NOT			$A \rightarrow B \rightarrow A$									
				1EKWISE SPE "H "P".	CIFIED IN THE SUF	FIX OF TH	E CAT.NO.					~ x\}/	/				
	М	IATERIAL:	HIG	H CONDUCTI	VITY WROUGHT CO	PPER						30					
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.														С		
							Beveled wire entry————————————————————————————————————										
_		INCTALLATION CHIPE							Wire inspection hole								
$\rightarrow$	INSTALLATION GUIDE DIE CODE = 54														$\leftarrow$		
	D	IE COLOR =	= Purple							( - + ± + + )	)— C						
														Die ¢	olor		
														/ <b>=</b>			
В									BC	DLT SIZE —	Color coded barr	el mar	kings				В
		)،	U) III	PallS													
		٠,		2002/95/EC													
			ISTED E CONNECTORS V/2/7/8.E513813														
																	—
										A	(R) CELES	TDA	<u></u>		D ATI	)NI	1
									+	HUYA	R 76. Hua						
				-						www.huyaco.co							
Α									DEF	EDINIC							
		WIRE CONNECTORS AND SOLDERING															
		LUGS FOR CODE AND FLEX CABLE															
		01-Dec-25		+			pec. Initialed.			MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	DA4034A-251			TS THE	RID ANGLE PI	ROJECTION	
ı	REV	DATE	DWN	CHK	DE:	SCRIPTIO	NC		ECN F	ELECTRO TIN PLATE	DWG. NO. 186-cp17	31	AIL IN	ICH .	<b>⊕</b> £		] ,
	4 3							4		2				1	-		
					•							•					