			_		1		_	<u></u>			1					
	THEIN	JEODMATION	4	WING IS THE I	PROERTY OF CELESTRA,	3		V OFLEGED	2	SIZE	POLT.	-	1	T	-	,
	DISCL	OSED IN CON	NFIDENCE AND T FOR WHICH F	NOT TO BE F	REPRODUCED, USED OR			CELESTR CAT.NO	• •	FLEX	BOLT SIZE	B MIN	C ±0.04	±0.01	D ±0.015	
	DIOLO	OLD EXOLIT	T T OIL WITHOUT	OKINOTIED.				DA4034A-2	261 4/0 AWG	550/24 = 222 kcmil 4/0 Weld	3/4	1.52	1.14	0.64	0.15	
													-		!	
D	l					. = 0.0 0= 1.1= 0.1.111										D
	N N	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.										Б.				
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE														
	LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.															
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS									В						
		OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".														
	М	IATERIAL:	HIGH	H CONDUCT	IVITY WROUGHT CO	PPER					00					
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE															С
	SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.						Beveled wire entry————————————————————————————————————									
								/—Wire inspection hole								
\rightarrow	INSTALLATION GUIDE DIE CODE = 54														\leftarrow	
		IE COLOR							- Huy)— C						
										I			Die ¢	olor		
_					./			В	OLT SIZE—	Color coded barr	el mar	kings				
В			c(VI	L)us	رRoHS،											В
			LIST	FN	2002/95/EC											
			WIRE CONNE ZMVV/2/7/8.E													
																_
		l	I I							0.00						
									HUYA	R CELES						
									www.huyaco.co							
Α							NNECTORS	CTORS AND SOLDERING								
							LUGS FOR CODE AND FLEX CABLE									
	00 01-Jul-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					tialed.	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION WROUGHT COPPER DA4034A-261 NTS									
ı	REV	DATE	DWN	СНК	DES	SCRIPTION		ECN F	FINISH ELECTRO TIN PLATE	DWG. NO. 186-cp17	38 ^{UI}	NIT IN	CH -	(4)		
			4			3		1	2				1			