	4		3	\downarrow		2		1						
Ι	DISCLOSED IN CON		HE PROERTY OF CELESTRA BE REPRODUCED, USED OR		CELES		WIRE CODE	SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	H ±0.01	D ±0.015	
					LA4038/	AP-260	4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/.0154	3/8	0.83	1.02	0.56	0.14	
D	NOTE:	1. ALL DIMENS SPECIFIED.	ONS ARE IN INCHES UN											
		LISTED BY "U	A,LB,WP AND J SERIES (JNDERWRITERS INC." A RES AND FLEX/24 STRA											
			NO.WITH "L" HAS NOT I SPECIFIED IN THE SUF											
С	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER C FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE							30.					С	
SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. Beveled wire entry														
\rightarrow	INSTALLATION GUIDE DIE CODE = 54 DIE COLOR = Purple					Wire inspection hole								
В		LISTED WIRE CONNECTORS ZMVV/27/8 E513813	RoHS		BOLT SIZE Color coded barrel markings									
					LUGS FOR CODE AND FLEX CABLE									
A													A	
	00 23-Aug-25 REV DATE	Ruby FengSinia QDWNCHK		tandards Spec. Initialed.	ECN	_	AL HIGH-CONDUCTIVITY WROUGHT COPPER	PRT. NO. LA4038AP-260		IT	-s	id angle pr		
	REV DATE	4 4		3	4 A		ELECTRO TIN PLATE	186-cp174	49	IN	сн 1	Ψ -		