									L								
			4				3		<u>/</u>	2			•	1			,
	DISCL	OSED IN CON	NFIDENCE AI	RAWING IS THE ND NOT TO BE F					CELESTR.	• •	SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	+0.01	D ±0.015	
	DISLO	SED EXCEPT	FOR WHICH	H FURNISHED.					LA4012AP-2		550/24 = 222 kcmil	1/2	1.12	1.19	0.65	0.16	
										4,07,000	4/0 Weld	1/2	1.12	1.10	0.00	0.10	ł
D																	D
	N	OTE:		L DIMENSION ECIFIED.	IS ARE IN IN	NCHES UNLES	S OTHERWISE						5				
	2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE																
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.															
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS											<del></del>					
			ОТ				OF THE CAT.NO.					ુ ×ંટ્રે					
	M	IATERIAL:			IVITY WRO	UGHT COPPE	R					30					
С	F	INISH:	EL	ECTOR-TIN P	LATE UNLE	SS OTHERWIS	SE										c
C		SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.							Beveled wire entry————————————————————————————————————								
									/—Wire inspection hole								
$\rightarrow$	INSTALLATION GUIDE DIE CODE = 54															$\leftarrow$	
		IE CODE =									)— c						
														Die ¢	olor		
									RO	OLT SIZE	Color coded barr	el mar	kinas	_/=			
В				V					В	JET SIZE			9-				В
		С		RoHS 2002/95/EC													
		WIF	LISTED RE CONNECTORS RVV/2/7/8.E513813														
										HUYA	® CELES						
				1						www.huyaco.co	_						
Α								_									A
	UGS FOR CODE AND FLEX CABLE																
	00	00 02-Dec-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.						ed	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION								
	REV	DATE	DWN	CHK			RIPTION	···	ECN F	WROUGHT COPPER FINISH ELECTRO TIN PLATE	LA4012AP-251  DWG. NO. 186-cp17	52 U	NIT	ICH .	<b>(</b>	$\exists$	
		I	4				3			2	'	$\dashv$		1	•		'
					'				l			1					