								1									
		4				3			7	2		1					
l	THE IN	THE INFORMATION ON THIS DRAWING IS THE P DISCLOSED IN CONFIDENCE AND NOT TO BE RE		OERTY OF CELESTRA, IS			CELESTRA	•	SIZE	BOLT	В	С	Н	D	1 '		
			T FOR WHICH		EPRODUCED, USED	OR			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.01	±0.015	1
									LA4012AP-20	61 4/0 AWG	550/24 = 222 kcmil 4/0 Weld	1/2	1.08	1.14	0.64	0.14	
										•	•						
D																	D
	N	IOTE:			S ARE IN INCHES	UNLESS (OTHERWISE										
				CIFIED.									D)			
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 											,	_			
	1	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS							$\frac{1}{B}$								
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																
												00,00					
	M	MATERIAL:	HIG	H CONDUCTI	VITY WROUGHT	COPPER						,					
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.														С		
							Beveled wire entry — H										
											nspection hole						
\rightarrow	INSTALLATION GUIDE														4		
	DIE CODE = 54 DIE COLOR = Purple																
		IL COLOR :	= Fulpie							1							
														Die (Color		
_					. /				BC	OLT SIZE	Color coded barr	el mai	kings				_
В			_(U) II S	Polls					21. 3.22			J				В
					2002/95/EC												
			LIS	TED NECTORS													
			ZMVV/2/7.	8.E513913													
	1																
		ı	I						1 1		<u> </u>						
										HUYA	® CELES					_	
										www.huyaco.com							
Α											,						A
^		TITLE WIRE CONNECTORS AND SOLDERING									^						
		LUGS FOR CODE AND FLEX CABLE						.E									
	00	0 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PRO. WROUGHT COPPER LA4012AP-261 NTS							ROJECTION			
	REV	DATE	DWN	СНК		ESCRIP	PTION		ECN FI	INISH ELECTRO TIN PLATE	DWG. NO. 186-cp17	54	NIIT	ICH	1		
		1	4				3	Λ		2		i		1			'
					ı			7				ı					