								ı									
			4				3	abla	7	2				1			
ı					ROERTY OF CELESTRA				CELESTRA			BOLT	В	С	Н	D	i '
		SED EXCEPT			EPRODUCED, USED OF	`			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.01	±0.015	
									LA4012AP-26	61 4/0 AWG	550/24 = 222 kcmil 4/0 Weld	1/2	1.08	1.14	0.64	0.14	
										1	-				-		
D																	D
_	N	IOTE:			ARE IN INCHES U	NLESS O	THERWISE										
			SPE	CIFIED.									D				
					,WP,AL,AS AND J S									-			
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.															
			PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS														
			OTH	HERWISE SPE	CIFIED IN THE SUF							ે ઝેં					
			WIT	H "P".													
	M	MATERIAL:	HIG	H CONDUCTI	VITY WROUGHT CO	OPPER						9)					
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.														С		
							Beveled wire entry — H										
_	I.	INSTALLATION GUIDE							Wire inspection hole								
	DIE CODE = 54																
	D	IE COLOR =	= Purple)— C						
											<u> </u>			Die ¢	color		
										/	Calar and ad hors		م م مانداه	/=			
В				,					ВС	OLT SIZE—	Color coded barr	ei mai	kings				В
		ر (PoHS													
		•	ICTED 00	2002/95/EC													
			LISTED E CONNECTORS VV/2/7/8.E513913														
											(R) CELES	TRΔ	CO	RPO	RATI	ON	
									 	HUYA	76. Hua						
				+					+	www.huyaco.com							
Α		TITLE WIRE CONNECTORS AND SOLE							DE	A PERING							
			LUGS FOR CODE AND FLEX CABLE														
		02-Dec-25		+ +			Spec. Initialed.			ATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	LA4012AP-261			TS THI	RID ANGLE P	ROJECTION	
ı	REV	DATE	DWN	CHK	DE	SCRIPT			ECN FI	ELECTRO TIN PLATE	DWG. NO. 186-cp17	54 U	nit In	ICH .	⊕ £		
	4 3 /							4	7 <u> </u>	2				1			
					-			ı				-					