		4		1	3	+	2		I		1									
1	DISCLOSED IN CO	NFIDENCE AND	NOT TO BE REPRO	RTY OF CELESTRA, IS DDUCED, USED OR		CELEST CAT.N	RA WIRE	SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	H ±0.01	D ±0.015	<b>i</b> '						
	DISLOSED EXCER	T FOR WHICH I	FURNISHED.			LA2538AF	2-251 250 kcmil	250 kcmil Class G 259 Str Class H 427 Str	3/8	1.01	1.28	0.70	0.17	ŀ						
D	NOTE:  1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.  2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE												D							
		LIST ON ( PRE OTH	ED BY "UNDERW CODE WIRES AN -FIX CAT.NO.WIT ERWISE SPECIF	B							_									
	WITH "P".  MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER							S X S												
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.  Beveled wire entry											С								
$\rightarrow$	INSTALLATION GUIDE DIE CODE = 62 DIE COLOR = Yellow						Wire inspection hole													
В	BOLT SIZE Color coded barrel markings													В						
	,	WRE CONNECTORS												_						
							HUYA www.huyaco.cor		ncun F	Rd. Zh	ongcu	ın Tow		N						
Α						WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE														
						FON	MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER FINISH	LA2538AP-251		ale NT	S	ID ANGLE PR	E PROJECTION							
	REV DATE	DWN 4	CHK	DESCR	3	ECN	electro tin plate	186-cp17	92   "	'' INC	1	₩ <u> </u>	7							