			4 3 2				<u> </u>		1			,								
·				AWING IS THE ND NOT TO BE					CELESTRA CAT.NO	WIRE		BOLT SIZE	A ±0.06	B MIN	C ±0.04	R	ID ±0.01			
				FURNISHED.					CAT.NO	CODE	FLEX 60 Navy #4 Weld		±0.06	IVIIIN	±0.04		±0.01	1		
									DA0214	2 AWG	125/24 = 50.5	1/4	1.50	0.65	0.59	0.85	0.30			
											kcmil							1		
D																		D		
	N/	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.								Color coded marking										
				2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE Bolt Size																
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE							Don Gize											
	ON CODE WIRES AND FLEX/24 STRANDED CABLES.								+											
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																		
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER																		
											. D									
С	1	INISH:		ECTOR-TIN P ECIFED PLAT							B B	-						С		
			SU	FFIX CAT.NO).WITH "S	P" FOR SILV	ER.		_	/	4	-								
									,			U								
\rightarrow		ISTALLATIO																4		
		IE CODE = : IE COLOR =								R	Inspecti	on Hol	е					7		
		il ooloit -	- DIOWII]-						_1_					
															6	7				
									₽, †					,	/ [
В			4			~ 2	V		<u> </u>					(В		
		c(VL)US 🗖	2 N	IEB	50	RoHS 2011/65/EU	ϵ		Bevele	d optry									
		LISTE	D	•				•		Devele	a entry									
		WIRE CONN	ECTOR																	
	L																	1		
										HUY	√ A® C	ELES	STRA	CO	RPOI	RATIO	NC			
								_			76. Huancun Rd. Zhongcun Town.									
										www.huyaco.com F					Panyu Dist. Guangzhou 511495.					
Α	H								TITLE WIRE CONNECTORS AND SO					SOI	oldering A					
	$\vdash \vdash \vdash$									LUGS FOR CODE AND FLEX CAB										
		00.4 55	Dut =	0: : 0:		0-1 (5		0		MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION								-		
				g Sinia Qiu				Spec. Initialed.	FON!	WROUGHT CO	DPPER DA	0214		N.	TS -	6 E	\neg			
ı	REV	DATE	DWN	CHK		DES	SCRIPT		ECN	ELECTRO TIN F	PLATE DWO. NO.	186-cp01	80 0	IN	ICH	Ψ L]		
			4				3	}	4	2					1					
									I											