			4				3	$\downarrow$	7	2				1			
ı		THE INFORMATION ON THIS DRAWING IS THE PI DISCLOSED IN CONFIDENCE AND NOT TO BE RE							CELESTRA			BOLT	В	С	Н	D	1 '
			TFOR WHICH		REPRODUCED,	USED OR			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	+	±0.015	1
							_		DA5158A	500 kcmil	500 Navy	5/8	1.58	1.61	0.88	0.22	1
D																	D
	NO	OTE:			S ARE IN INC	CHES UNLES	S OTHERWISE						_				
			SPE	CIFIED.								ı	D				
							AT.NO.S ARE						]				
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.															
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS										l —						
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.									&×ÿ	/						
			WIT	H "P".								<i>3</i> 20					
	M	ATERIAL:	HIG	H CONDUCT	IVITY WROU	GHT COPPE	R										
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE						Beveled wire entry — H								С		
	SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.								Bovolod Wile Only								
									Wire inspection hole								
$\rightarrow$	IN	STALLATIO	ON GUIDE	IDE													
	DIE CODE = 87 DIE COLOR = Brown																
		L COLOR :	= BIOWII								\ <u>\</u>			Die C	Color		
											0.1			/=			
_					. /	,			BC	OLT SIZE—	Color coded barr	ei ma	rkings				_
В			_(Ս	) IIc		•											В
					2002/95/EC	ľ											
			LIS WIRE CON			•											
			ZMVV/2/7/8	I.E513913													
	ł																l —
	<u> </u>		I						1 1								
			-							HUYA	® CELES					_	
										www.huyaco.com						n.	
Α								_	<u> </u>								Α
, ,		TITLE WIRE CONNECTORS AND SOLDERI										l ^`					
		LUGS FOR CODE AND FLEX CABL							.E								
	00	23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.				ed.	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE WROUGHT COPPER DA5158A NTS						RID ANGLE PE	ROJECTION			
ı	REV	DATE	DWN	СНК		DESCR	RIPTION		ECN F	ELECTRO TIN PLATE	DWG. NO. 186-cp18	70	NIT	СН	<b>(</b> ) E	$\exists$	
	4 3						$\triangle$		2		i		1			'	
					ı							'					