								\perp				ī					$\overline{}$
			4				3			2			1		1		,
	DISCLO	THE INFORMATION ON THIS DRAWING IS THE F DISCLOSED IN CONFIDENCE AND NOT TO BE F					CELESTR. CAT.NO				BOLT B C H SIZE MIN ±0.04 ±0.01 ±0			D ±0.015			
	DISLOS	SED EXCEPT	FOR WHICH	FURNISHED.					LA6158A	+	-	5/8	1.58	1.75		0.24	
								,			-						
_																	_
D	N/	OTE:	1 ΔΙΙ	DIMENSION	S ARE IN INCHE	S I INI ESS	OTHERWISE										D
		OIL.		CIFIED.	O AIL IN INOTIL	O UNLLOS	OTTLKWISE						D	-			
					B,WP AND J SER								1—‡				
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.															
									$A \rightarrow B_{\circ}$								-
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.																
		WITH "P".															
	M	ATERIAL:	HIG	H CONDUCT	IVITY WROUGH	COPPER											
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE							Beveled wire entry——H								С	
	SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.								Bovoica wife entry								
									Wire inspection hole								
\rightarrow	IN	INSTALLATION GUIDE															4
	DIE CODE = 94 DIE COLOR = Green														7		
			0.00								J <u>V</u> _			Die (Color I		
									D/	OLT 0175	Color coded barr	el mai	rkinas				
D					./				BC	OLT SIZE—	Color coded barr	Cillia	Kirigs				Ь
В			c(V	L)us	.RoHS.												В
			HC	TED .	2002/95/EC												
			WIRE CONI														
																	-
											(R) CELES	TRA	CO	RP∩	RΔTI	ON	
									+	HUYA	76. Hua						
									+	www.huyaco.co							
Α								TITLE WIRE CONNECTORS AND SOLDERING '								Α	
	\vdash	LUGS FOR CODE AND FLEX CABLE															
		00 24-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE							PROJECTION			
	00 REV	24-Aug-25 DATE	Ruby Feng	Sinia Qiu CHK		DESCRIF		•		WROUGHT COPPER	LA6158A	20	NIIT	TS		\neg	
	NEV	DAIE	4	CHK	<u> </u>	DESCRIP	3	<u></u>	CIN	ELECTRO TIN PLATE	186-cp19	JU	IN.	ICH /	1		1
	4 3							4	7	۷					I		