			4				3	\downarrow	7		2					1					
I	DISCL	OSED IN CON	VFIDENCE ANI	D NOT TO BE	PROERTY OF CEL REPRODUCED, US				CELESTRA CAT.NO		WIRE	SIZE FL	EX	BOLT SIZE	B MIN	C ±0.04	H ±0.01	D ±0.015	5		
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.]		LA6138AP-2	260	600 kcmil	+	-	3/8	0.83	1.74	0.93	0.26	1		
D	N	IOTE:	1 ΔΙΙ		NS ARE IN INCH		OTHERWISE												D		
		IOTE.		CIFIED.		LO UNLLOO	OMERWISE					1		1	D						
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE 																			
		ON CODE WIRES AND FLEX/24 STRANDED CABLES.																			
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.																				
	WITH "P". MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER										90										
С		INISH:																			
C	SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.								Beveled wire entry H												
2							Wire inspection hole														
\rightarrow	> INSTALLATION GUIDE DIE CODE = 94																				
	DIE COLOR = Green										Die Co	olor									
						BC	BOLT SIZE Color coded barrel markings														
В			ີດ																В		
					2002/95/EC																
			LIS WIRE CON ZMVV/2/7/8																		
																			-		
										Η	UYA	®	76. Hua								
									+		w.huyaco.cor	_	Panyu D						A		
A										WIRE CONNECTORS AND SOLDERING											
										LUGS FOR CODE AND FLEX CABLE MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION									_		
	00 Rev	23-Aug-25 DATE	Ruby Feng	Sinia Qiu CHK	Cele	estra Standar DESCRII	ds Spec. Initialed.			FINISH	WROUGHT COPPER	PRT. NO. LA6' DWG. NO.	138AP-260	_	N.	TS -			1		
	ΓĽV	DATE	4			DESCKI	3	1			ELECTRO TIN PLATE		186-cp190	05	IN	існ 1	Ψ		J		
			Т		1		~	4			-			Ι		I					