		4		3	$\downarrow$	2		1		1			
ı	DISCLOSED IN CON	ON THIS DRAWING IS THE FIDENCE AND NOT TO BE FOR WHICH FURNISHED.	PROERTY OF CELESTRA, REPRODUCED, USED OR	IS	CELEST CAT.N		SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	H ±0.01	D ±0.015	
	DISLOSED EXCEPT	FOR WHICH FORNISHED.			DA7558A	-260 750 kcmil	1325/24 = 535 kcmil	5/8	1.33	1.91	1.03	0.27	
D	NOTE:	ALL DIMENSION     SPECIFIED.	NS ARE IN INCHES UNL	LESS OTHERWISE									D
		LISTED BY "UN ON CODE WIRE PRE-FIX CAT.N	DERWRITERS INC." AN ES AND FLEX/24 STRAN O.WITH "L" HAS NOT P	NDED CABLES. EEP HOLE UNLESS		D B							
		WITH "P".	PECIFIED IN THE SUFF										
С	MATERIAL: FINISH:	ELECTOR-TIN I SPECIFED PLA	TIVITY WROUGHT COF PLATE UNLESS OTHER TE PER MIL - T -16366. D.WITH "SP" FOR SILVE	E	Beveled wire entry H								
<b>→</b>	INSTALLATION GUIDE DIE CODE = 99 DIE COLOR = Pink					Wire inspection hole							
В	c <b>(</b>	US ROHS			I	BOLT SIZE	Color coded bar	rel maı	rkings	Je v			В
		ISTED CONNECTORS VIZITHE ES13813											
						HUY/ www.huyaco.co		ancun	Rd. Zh	nongcı	un Tow	n.	
Α					WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								
		Ruby Feng Sinia Qiu	ļ	andards Spec. Initialed.	501	MATERIAL HIGH-CONDUCTIVIT WROUGHT COPPER FINISH	DA7558A-260		NIT	TS .	RID ANGLE PF	ROJECTION	
	REV DATE	DWN CHK	DES	CRIPTION 3	ECN	ELECTRO TIN PLATE	186-cp19	914   "	IN	CH   1	9 -		