		4		I		3	7	7	2		1		1			
I	THE INFORMATION ON THIS DRAWING IS THE PROERTY OF CELESTRA, IS DISCLOSED IN CONFIDENCE AND NOT TO BE REPRODUCED, USED OR					CELESTRA WIRE SIZ		1	BOLT	В	C	Н	D			
		EPT FOR WHICH						CAT.NO WP9158A-047	CODE 7 900 kcmil	FLEX 1925/24 = 777	SIZE 5/8	MIN 1.80	±0.04 2.18	±0.01	±0.015 0.33	
								WF9130A-047	7 900 KCIIII	kcmil	5/0	1.00	2.10	1.10	0.55	
D																D
	NOTE:		DIMENSION	NS ARE IN INCHES	UNLESS O	THERWISE						_				
				B,WP AND J SERIE								D v				
				DERWRITERS INC.' S AND FLEX/24 ST												
				O.WITH "L" HAS NO PECIFIED IN THE SI												
			H "P".			THE CATINO.		A B A B A B A B A B A B A B A B A B A B								
	MATERIA			TIVITY WROUGHT (9 ⁵					
С	SPECIFED PLATE PER MIL - 1 -16366.															
		SUF	FIX CAT.NC).WITH "SP" FOR SI	LVER.		Deve	Beveled wire entry — H								
						Wire inspection hole										
\rightarrow		INSTALLATION GUIDE DIE CODE = 115														
		DR = Yellow														
										V			Die Co	blor		
В								BOLT SIZE $-$ Color coded barrel markings $-$								В
		C C	J us	RoHS												
		ZM///2/7/	8.E513913													
								I	HUYA	© CELES						
									www.huyaco.cor						'n.	
А								WIRE CONNECTORS AND SOLDERING								А
						LUGS FOR CODE AND FLEX CABLE										
	00 23-Aug	25 Ruby Feng	Sinia Qiu	Celestra	a Standards	Spec. Initialed.			TERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	WP9158A-047			TS THR			
I	REV DAT		СНК		DESCRIPT		Л			DWG. NO. 186-cp19	30	NIT IN	СН -	⊕ L		
		4				3	4		2				1			