								ı									
			4				3	4	7	2				1			
1					PROERTY OF CELES				CELESTRA			BOLT	В	С	Н	D	'
		SED EXCEPT			EPRODUCED, USED	OR			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.01	±0.015	
							-		LA4538AP-2	51 -	444.4 kcmil 450 FLEX 1100/24	3/8	1.52	1.70	0.92	0.26	
											1		l		1		Ì
D																	D
D	N	IOTE:	1. ALL	DIMENSIONS	S ARE IN INCHES	UNLESS	OTHERWISE										
				CIFIED.									Ь				
			2. ALL	DA,DB,LA,LB	B,WP,AL,AS AND	SERIES	OF CAT.NO.S A	RE					Ĺ	-			
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.															
											21		7 4				 —
					.WITH "L" HAS NO ECIFIED IN THE S							В	'/				
				H "P".		0111701	THE OAT NO.					~ ×'n	/				
	M	MATERIAL:	HIG	H CONDUCTI	VITY WROUGHT	COPPER						ðη.					1
_																	
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.						Reveled wire entry H								С		
			SUF	FIX CAT.NO.	WITH "SP" FOR S	ILVER.			Be/	veled wire entry —	, 11						
									∕—Wire inspection hole								
\rightarrow	INSTALLATION GUIDE														4		
	DIE CODE = 80 DIE COLOR =													7			
		IL COLOR =															
														Die ¢	olor		
									D.C	N T 017E	Color coded barr	el mai	kinas				
В									ВС	OLT SIZE—	Color coded barr	Cilliai	Kings				В
		c((UL) _{US}	RoHS													
		•	ICTED	2002/95/EC													
			E CONNECTORS VV/2/7/8.E513913														
										A	© CELES	TD A	<u></u>	DDO	DATI	ON	1
				+					+	HUYA	R) CELES					_	1
				-						www.huyaco.com							1
Α								-			,						Α
, ,		WIRE CONNECTORS AND SOLDERING									`						
	LUGS FOR CODE AND FLEX CABLE							L		1							
	00	02-Dec-25	Ruby Feng	Feng Sinia Qiu Celestra Standards Spec. Initialed.				i.	М	ATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	PRT. NO. LA4538AP-251	S	CALE N	TS ТНІ	RID ANGLE P	ROJECTION	
	REV	DATE	DWN	CHK	[DESCRI	PTION		ECN FI	NISH ELECTRO TIN PLATE	DWG. NO. 186-cp19		NIIT	ICH	D E		
			4	1			3	Δ	\	2	<u>'</u>	1		1	-		'
			•		ı		_	4	Ľ	_		1					