	•							1									
			4				3		7	2				1			
I					PROERTY OF CE				CELESTRA	· -	SIZE	BOLT	В	С	Н	D] '
				FURNISHED.	REPRODUCED, L	ISED OK			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.01	±0.015	4
5							-		DA5158A-24	-	1100/24 = 444 kcmil 500 Weld 59/.0417 427/.0325 703/.0253	5/8	1.58	1.75	0.96	0.24	
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.												D				
	2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".										<u>D</u>						
	М	IATERIAL:	HIG	H CONDUCT	IVITY WROUG	HT COPPER						~0°,x/2)	/				
С	FI	INISH:			LATE UNLESS E PER MIL - T		E					O)e					С
					.WITH "SP" FC												
		Beveled wire entry————————————————————————————————————															
INSTALLATION CLUDE																	
	INSTALLATION GUIDE DIE CODE = - DIE COLOR = Pink							Wire inspection hole									
										Huys)— C			Die			
В																	В
		c(RoHS					ВС	DLT SIZE—	Color coded barı	el mar	kings				
			ISTED E CONNECTORS	Loverage													
			VV/2/7/8.E513813														
	1																-
										111137 4	(R) CELES	TRA	CO	RPO	RATI	ON	1
										HUYA	76. Hua	incun	Rd. Zh	nongcı	ın Tow	'n.	
А									www.huyaco.com Panyu Dist. Guangzhou 511495.							A	
^		TITLE WIRE CONNECTORS AND SOL							EKING								
										AND FLEX CABLE							
				Sinia Qiu	Се		rds Spec. Initialed.			ATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	DA5158A-241	<u> </u>		TS THR	RID ANGLE P	ROJECTION	
1	REV	DATE	DWN	CHK		DESCRI			ECN F	ELECTRO TIN PLATE	DWG. NO. 186-cp19	48	nit IN	CH	Ψt]
			4				3	4	7	2				1			