	_	4		I	3	\downarrow		2		1		1			
ı	DISCLOSED IN	TION ON THIS DRAY CONFIDENCE AND CEPT FOR WHICH F	NOT TO BE REPR	ERTY OF CELESTRA, IS ODUCED, USED OR		CELE		WIRE CODE	SIZE FLEX	BOLT SIZE	B MIN	C ±0.04	H ±0.01	D ±0.015	l
	DISLOSED EX	CLF I I OR WITICITE	OKINISHED.			LA5138	AP-261	-	535.3 kcmil 1325/24 500 kcmil	3/8	0.83	1.81	0.98	0.27	
D	NOTE:		DIMENSIONS AF	RE IN INCHES UNLES	S OTHERWISE						D				D
	2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS												_		
		OTHI WITH		FIED IN THE SUFFIX (OF THE CAT.NO.										
С	MATERI FINISH:	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366.													
				H "SP" FOR SILVER.			Bevele	d wire entry —	H						
	INSTALLATION GUIDE DIE CODE = - DIE COLOR = Pink						Wire inspection hole								
В		C UL US	RoHS				BOLT	SIZE	Color coded barr	el mar	kings	Die ¢c	olor		В
		LIS IEU WIRE CONNECTORS ZMAY/27/76.E513813													
								IUYA ww.huyaco.cor		ncun	Rd. Zh	nongci	ın Tow		
А						WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									
	00 01-De				ards Spec. Initialed.			AL HIGH-CONDUCTIVITY WROUGHT COPPER	LA5138AP-261		DALE N	ΓS -	RID ANGLE PF	ROJECTION	
	REV DA	4	CHK	DESCH	3	ECN	1,141011	electro tin plate	186-cp19	59 5	IN	СН 1	9 -		