								ı									
			4				3	4	7	2				1			
1					PROERTY OF CELESTE				CELESTRA	·	SIZE	BOLT	В	С	Н	D	'
		SED EXCEPT			EPRODUCED, USED C	JR			CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.01	±0.015	1
									DA7512A-25	51 -	777.7 kcmil 1925/24	1/2	1.38	2.17	1.17	0.32	
										!	•				1		
D																	D
_	N	IOTE:		DIMENSIONS	S ARE IN INCHES U	JNLESS (OTHERWISE						_				
			2. ALI	DA.DB.LA.LE	B.WP.AL.AS AND J	SERIES (OF CAT.NO.S AI	RE			I	I		_			
		2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE															
		ON CODE WIRES AND FLEX/24 STRANDED CABLES.															 —
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.															
				1EKWISE SFI H "P".	ECIFIED IN THE 30	IFFIX OF	THE CATINO.					~ x\	/				
	M	MATERIAL:	HIG	H CONDUCT	IVITY WROUGHT C	OPPER						00					
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.														С		
							Beveled wire entry — H										
_		INSTALLATION GUIDE							Wire inspection hole								1
	DIE CODE = 106																
	D	IE COLOR =	= Black)— C						
											J			Die (Color		
											0-1						
В				,					ВС	OLT SIZE —	Color coded barr	ei mai	Kings				В
		c	UI) _{IIC}	Dalle													
				2002/95/EC													
			LISTED RECONNECTORS VV/2/7/8.E513913														
																	1
	1																
										A	(R) CELES	TD A	<u></u>	DD0	DATI	ONI	1
				+ +					+	HUYA	76. Hua						1
										www.huyaco.co							1
Α							WIRE CONNECTORS AND SOLDERING							Α			
										1							
								CODE AND FLEX CABLE									
		02-Dec-25		+			ls Spec. Initialed			IATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER	DA7512A-251			TS TH	RID ANGLE F	ROJECTION	
ı	REV	DATE	DWN	CHK	D	ESCRIP	TION		ECN FI	ELECTRO TIN PLATE	DWG. NO. 186-cp19	69 U	11 11	1CH	⊕ €		1
	4 3						4	7 <u> </u>	2				1		-		
					•			I				•					