		1		1	3	+	2		1		1			
	THE INFORMA	TION ON THIS DRA	AWING IS THE PRO	DERTY OF CELESTRA, IS		CELEST	RA WIRE	SIZE	BOLT	В	С	Н	D	]
		CONFIDENCE AN CEPT FOR WHICH		RODUCED, USED OR		CAT.NO	CODE	FLEX	SIZE	MIN	±0.04	±0.01	±0.015	ļ
D					_	DA4056A-	241 -	4/0 Weld 550/24 = 222 kcmil 133/.0399 259/.0286 637/.0183	5/16	0.88	1.25	0.64	0.15	D
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.													
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.													
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".													
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER							/						
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.										С			
	Beveled wire entry————————————————————————————————————													
$\rightarrow$	INSTALL													
	DIE CODE = 62 DIE COLOR = Yellow  Wire inspection hole													
В	CULUS BOLT SIZE Color coded barrel markings  BOLT SIZE Color coded barrel markings													В
_														
		1												
							HUYA www.huyaco.com		ncun R	Rd. Zh	ongcu	ın Tow		
Α							TITLE WIRE CONNECTORS AND SOLDERING							Α
							LUGS FOR CODE AND FLEX CABLE							
	00 23-Aug	00 23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECT DA4056A-241 NTS							
1	REV DAT	E DWN	CHK	DESCR		ECN	FINISH ELECTRO TIN PLATE	DWG. NO. 186-cp19	74 UN	IT IN(	CH +	(H) E	$\rightarrow$	] ,
		4			3	$\triangle$	2				1			