		4		3	\downarrow	2			1		
1	DISCLOSED IN CO	N ON THIS DRAWING IS THE P NFIDENCE AND NOT TO BE R T FOR WHICH FURNISHED.		S	CELEST CAT.N	101	SIZE FLEX	BOLT B		D 1 ±0.015	
D	NOTE:	1. ALL DIMENSIONS	S ARE IN INCHES UNL	ESS OTHERWISE	DA3512A	-241 -	350 Weld 259/.0368 427/.0285 703/.0224 889/.0201 373.7 kcmil	1/2 1.2	5 1.61 0.79	0.22 D	
	SPECIFIED. 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".										
С	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.								С		
→	Beveled wire entry INSTALLATION GUIDE DIE CODE = 71 DIE COLOR = Red Wire inspection hole										
В									В		
										-	
						HUYA www.huyaco.co	76. Hua	ncun Rd.	ORPORAT Zhongcun To gzhou 51149	wn.	
А						WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE					
	00 23-Aug-25	Ruby Feng Sinia Qiu DWN CHK		ndards Spec. Initialed.	ECN	MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER FINISH	DA3512A-241	SCALE UNIT	NTS A	PROJECTION	
	NEV DATE	4		3	4	ELECTRO TIN PLATE	186-cp19	01	1 1		