		4		3	\downarrow	2		1	1		
ı	DISCLOSED IN CO	N ON THIS DRAWING IS THE F NFIDENCE AND NOT TO BE R	PROERTY OF CELESTRA, IS EPRODUCED, USED OR		CELEST CAT.N		SIZE	BOLT SIZE	B C MIN ±0.04	H D ±0.015] '
D	NOTE:		S ARE IN INCHES UNLE	SS OTHERWISE	DA3512A		350 Weld 259/.0368 427/.0285 703/.0224 889/.0201 373.7 kcmil	1/2	1.25 1.61	0.79 0.22	D
	SPECIFIED. 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".									_	
С	MATERIAL: FINISH:	ELECTOR-TIN PL SPECIFED PLATI	VITY WROUGHT COPF LATE UNLESS OTHERV E PER MIL - T -16366. WITH "SP" FOR SILVER	/ISE		90° ***3					
	Beveled wire entry————————————————————————————————————										
	INSTALLATION GUIDE DIE CODE = 71 DIE COLOR = Red Wire inspection hole								\leftarrow		
В	BOLT SIZE Color coded barrel markings								В		
_		ZMVVW/NLESTJBIS									_
						HUYA www.huyaco.com	76. Hua	incun Ro	CORPOR d. Zhongcu angzhou 51	n Town.	
А						WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE					
		Ruby Feng Sinia Qiu		dards Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER FINISH	DA3512A-241	SCAL	NTS	D ANGLE PROJECTION	ī
	REV DATE	DWN CHK	DESC	RIPTION 3	ECN	ELECTRO TIN PLATE	186-cp19	81 UNIT	INCH 1	¥ <u> </u>	J
		- T	I	J	4	<u>~</u>		I	'		