		4 3		0	1									
			PROERTY OF CELESTRA, IS	3	CELESTRA	2 WIRE SIZE		BOLT		вС	D	G H	1	
		FIDENCE AND NOT TO BE F FOR WHICH FURNISHED.	REPRODUCED, USED OR		CAT.NO	CODE	FLEX	SIZE :	±0.06 M	IIN ±0.04	±0.015 ±	0.02 ±0.01	_	
				_	LB141458P-260	14-10 AWG	-	1/4	2.13 1.	27 0.41	0.05	0.63 0.17	1	
D	NOTE:	1 ALL DIMENSION	C ADE IN INCHES LINES	e OTHEDWise									D	
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.													
		2. ALL DA,DB,LA,LI	_	Color coded barrel markings										
		LISTED BY "UND ON CODE WIRE	/—BOLT SIZE											
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS													
		OTHERWISE SP WITH "P".	ECIFIED IN THE SUFFIX C	OF THE CAT.NO.		0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0		C C						
	MATERIAL:	HIGH CONDUCT												
С	FINISH:	ELECTOR-TIN P	-G								С			
O	SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.							A						
	—Wire inspection hole													
\rightarrow	INSTALLATIO	H B B												
	DIE CODE = - DIE COLOR =													
						[∖] _Bev	eled wire entr	ry	D					
В		• ./											В	
	c (UL) US ROHS												
	LI	ISTED CONNECTORS												
	ZMV	V/2/7/8 E513913												
							JYA [®]	CE	LEST	RA CO	RPOR/	NOITA		
				-			ıyaco.com			un Rd. Zh				
А											A			
, ,				LUGS FOR CODE AND FLEX CABLE										
	00 03-Nov-25	· •	Celestra Standa	FON	WROUGHT COPPER LB141458P-260 NTS							N		
	REV DATE	DWN CHK	DESCR		ECN	ELECT	RO TIN PLATE	180	6-cp2008	I IN	ICH 4]	
		4	I	3	4	2					I			