	-	4		1	2	47		0			1		4			
	THE INFORMA	TION ON THIS DRA	AWING IS THE F	PROERTY OF CELESTR	3 A, IS	CELESTRA	2 WIRE SIZE		BOLT	А	В	С	D	G	Н	
	DISCLOSED IN		D NOT TO BE F	REPRODUCED, USED O		CAT.NO	CODE	FLEX	SIZE	±0.06	MIN	±0.04	±0.015	_	±0.01	
						DB081058	8 AWG	#8 Weld 37/24 = 14.9 kcmil	#10	1.85	1.18	0.42	0.08	0.63	0.22	
								•	•	•		•	•	•		
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. 2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE															D
		LIS	ΓED BY "UND	ERWRITERS INC." S AND FLEX/24 STR		Color coded barrel markings BOLT SIZE										
		OTH).WITH "L" HAS NOT ECIFIED IN THE SU												
	MATERI	AL: HIG	H CONDUCT	IVITY WROUGHT C	OPPER		Die				7					
С	FINISH:	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. A (S)											С			
	DIE COD	ATION GUIDE E = 21 OR = Red			I	Wire inspection hole H P B I I I I I I I I I I I I										
В		C U		RoHS, 2002/96/EC			Ве	eveled wire entr	y	I	Ď					В
	-	ZMVVZII	B.E513913													
								JYA® nuyaco.com	7	'6. Hua	incun	Rd. Zh	nongci	RATION Un Tow 11495.	_	
Α						WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
	00 23-Aug	-25 Ruby Feng	Sinia Qiu	Celestra	Standards Spec. Initialed.	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE WROUGHT COPPER DB081058 NT								RID ANGLE PF	ROJECTION	
1	REV DAT	E DWN	СНК	DE	SCRIPTION	ECN	FINISH ELEC	CTRO TIN PLATE	9. NO. 1	86-cp20	10	nit In	CH -	₩ £	\Box	ı
		4			3	\uparrow		2					1			