			4		-		3		+		2					1							
I						OF CELESTRA, IS CED, USED OR			CELESTRA CAT.NO	WIRE SIZE CODE FLEX		BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01					
	DISLO	SED EXCEPT	FOR WHICH I	FURNISHED.					DB081058-242	8 AWG	#8 Weld 37/24 =		1.85	1.18	0.41	0.06	0.63	0.22					
											14.9 kcmil												
D		OTE	4 11	DIMENIOION	IO ADE IN		OO OTHERWIN	_											D				
	l N	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.								Colon and add hours!													
	LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.									/	Color coded barrel markings BOLT SIZE												
										/													
			OTH			." HAS NOT PEE IN THE SUFFIX	Hursen C																
	M	MATERIAL:	HIGH	H CONDUCT	TIVITY WF	ROUGHT COPPE																	
С	F	INISH:	SPE	CTOR-TIN F CIFED PLA ^T FIX CAT.NC		A—————————————————————————————————————																	
		—Wire inspection h																					
		NSTALLATIO	ON GUIDE						B B														
	DIE COLOR = Red								\subseteq	Ψ H			7										
_		Beveled wire entry															_						
В			c (₩	L)us	Rol	HS,													В				
			LIST	TED .	2002/9	95/EC																	
			WIRE CONN ZMVV/2/7/8																				
																			—				
										ш		С	ELES	TRA	CO	RPOI	RATIO	ON					
										HUYA® Www.huyaco.com CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495. TITLE WIRE CONNECTORS AND SOLDERING													
Α																			Α				
										LUGS FOR CODE AND FLEX CABLE													
	00	0 04-May-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					aled.			H-CONDUCTIVITY PRI	. NO. DB081	058-242		CALE N		RID ANGLE PE	ROJECTION	CTION					
1	REV	DATE	DWN	СНК		DESC	RIPTION		ECN		CTRO TIN PLATE	G. NO. 1	86-cp20	11	nit In	iCH -	⊕ £	\rightarrow					
			4				3		\triangle		2					1							