		4		1		0	+		0			1		4								
	THE INFORMATION	4 3 NFORMATION ON THIS DRAWING IS THE PROERTY OF CELESTRA, IS		3	CELESTRA	2 WIRE SIZE		BOLT	Α	В	С	1	G	Н								
	DISCLOSED IN CON	VFIDENCE AND	NOT TO BE R				CAT.NO	CODE	FLEX	SIZE	±0.06	MIN	±0.04	1	_	±0.01						
	5.02.002.5					_	LB081434	8 AWG	#8 Weld 37/24 = 14.9 kcmil	1/4	2.19	1.27	0.47	0.06	0.75	0.22						
									1 110 11011111	ı			!				l					
D																	D					
	NOTE:		DIMENSION: CIFIED.	S ARE IN INCH																		
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE —Color coded barrel markings																				
				ERWRITERS IN S AND FLEX/24		Color coded barrel markings																
	-	PRF-	FIX CAT NO).WITH "L" HAS	NOT PEEP		_BOLT SIZE															
			ERWISE SPI			F THE CAT.NO.																
	MATERIAL:			IVITY WROUGH	AT CODDE		Huga - C															
_	FINISH:			LATE UNLESS																		
С	FINISH.	SPEC	CIFED PLAT	E PER MIL - T -	16366.	L			∇—	G—∽							С					
		2011	TA CAT.NO.	WITH "SP" FOF	K SILVER.			∇	——A——		— ⊳											
\rightarrow	INSTALLATIO			-Wire inspection hole																		
	DIE CODE = DIE COLOR :							H		В	\rightarrow	I	/		\		7					
								1				<u> </u>	\in		\Rightarrow							
								\		I)		ı								
В		. (ii)	V				\B€	eveled wire entr	У							В					
		C	JU S	RoHS 2002/95/EC																		
		LIST WIRE CONNE	ED ECTORS																			
		ZMVV/2/7/8.E	513913																			
	1																—					
										C	FIFS	TRA	CO	RPOI	RATIO	NC						
									JYA®	7	'6. Hua	ncun	Rd. Zh	nongcı	ın Tow	_						
A									nuyaco.com	F	anyu [Dist. G	uangz	hou 5	11495.		_					
Α						TITLE WIRE CONNECTORS AND SOLDER								l A								
								LUGS FOR CODE AND FLEX CABLE														
	00 23-Aug-25	Ruby Feng	Sinia Qiu	Cele	stra Standa	rds Spec. Initialed.		WR	H-CONDUCTIVITY PRT OUGHT COPPER	LB0	81434			TS THE	RID ANGLE PROJECTION							
1	REV DATE	DWN	CHK		DESCRI		ECN		CTRO TIN PLATE	G. NO. 1	86-cp20	46	NIT IN	СН	₩ L	ightharpoons						
		4				3	\triangle		2					1								
							ı															