	•		_						+				ı						
	THEIN	IEODMATION	ON THIS DD	AWING IS THE	DDOEDTY O	F CELESTRA, IS	3		<u>V</u>	2 WIRE SIZE		5017	<u> </u>		1			,	
	DISCL		IFIDENCE AN	D NOT TO BE					CELESTRA CAT.NO	CODE	FLEX	BOLT SIZE	+0.06	B MIN	±0.04	R	ID ±0.01		
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.					WP0214-053	2 AWG	60 Navy #4 Weld 125/24 = 50.5 kcmil	1/4	1.69	0.55	0.59	0.84	0.30		
D	N	OTE:		DIMENSION	IS ARE IN	INCHES UNLE	SS OTHERWISE	Ē		Color coded marking									
			LIST	 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. 					Bolt Size										
	-		OTH				EP HOLE UNLES OF THE CAT.NO		DIE CODE										
	М	IATERIAL:	HIG	H CONDUC	ΓΙVITY WR	OUGHT COPPI	ER		1										
С	FI	INISH:	SPE	CIFED PLA	ΓE PER MII	ESS OTHERW L - T -16366. " FOR SILVER.			-		B	-						С	
→	INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown R Inspection Hole															\leftarrow			
В		LISTE)	: ^ N	IEB	s3 🖫		E		Beveler	d entry			E				В	
		WIRE CONN	ECTOR																
	1																	<u> </u>	
										HUY www.huyaco	A	ELES 76. Hua Panyu I	ancun	Rd. Zh	nongci	ın Tow			
Α										WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									
	00	23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.				aled.		MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJUCTIVITY WROUGHT COPPER WP0214-053 NTS							ROJECTION				
1	REV	DATE	DWN	СНК		DESC	RIPTION		ECN	FINISH ELECTRO TIN F	51440 140	86-cp02	.06	nit IN	CH -	() E			
			4				3		4	2			İ		1				