	-		4		I		3	\downarrow		2					1			
I	DISCL	OSED IN CON	IFIDENCE ANI	D NOT TO BE I		CELESTRA, IS D, USED OR		CELESTRA CAT.NO	W CODE	IRE SIZE	BOLT SIZE	A ±0.06	B MIN	C +0.04	D ±0.015	G ±0.02	H ±0.01	
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.				LB081058P-251	8 AWG	#8 Weld 37/24 =	#10	2.04	1.17	0.41	0.08	0.63	0.23	
										14.9 kcmil		_		-				
D	N	IOTE:	2. ALL LIST ON 0	CIFIED. DA,DB,LA,L ED BY "UNI CODE WIRE	B,WP AND DERWRITEI S AND FLE	J SERIES OF C RS INC." AND "(X/24 STRANDE	CSA" FOR USE	Color coded barrel markings										D
	M	IATERIAL:	OTH WIT	IERWISE SP H "P".	PECIFIED IN		Die Color											
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С					
\rightarrow	INSTALLATION GUIDE DIE CODE = 21 DIE COLOR = Red							Wire inspection hole										\Leftrightarrow
В	Beveled wire entry														В			
	1																	—
A								HUYA® www.huyaco.com CELESTRA CORPO 76. Huancun Rd. Zhongcu Panyu Dist. Guangzhou 5							in Tow			
								TITLE WIRE CONNECTORS AND SOLDERING A LUGS FOR CODE AND FLEX CABLE A										
		-					ards Spec. Initialed.			OUGHT COPPER		58P-251		CALE NT	rs –	ID ANGLE PR		
	REV	DATE	DWN 4	СНК	I	DESCR	3	ECN	ELE	CTRO TIN PLATE	^{3. NO.} 1	86-cp20	68 ^U I	IN	сн / ' 1	ΨĽ		
	-		4				J	4		<u> </u>			Ι		1			