			4				3	\downarrow		2					1			
I	DISCL	OSED IN CON	FIDENCE ANI	D NOT TO BE	PROERTY OF CEI REPRODUCED, U	LESTRA, IS SED OR		CELESTRA CAT.NO	W CODE	IRE SIZE	BOLT SIZE	A ±0.06	B MIN	C +0.04	D ±0.015	G ±0.02	H ±0.01	
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.				LB081034P-251	8 AWG	#8 Weld 37/24 = 14.9 kcmil	#10	2.16	1.29	0.41	0.08	0.75	0.23	
										14.9 KCIIII								
D	N	IOTE:	DTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.													D		
			2. ALL LIST	DA,DB,LA,L ED BY "UNI	B,WP AND J SE DERWRITERS I S AND FLEX/24	INC." AND "(CSA" FOR USE	Color coded barrel markings										
			OTH		D.WITH "L" HAS PECIFIED IN TH													
	М	IATERIAL:	HIGI		FIVITY WROUG	HT COPPE	2											
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.										С						
\rightarrow	INSTALLATION GUIDE DIE CODE = 21 DIE COLOR = Red							Wire inspection hole										\Diamond
В					RoHS				Be	eveled wire entr	у	[\mathbf{b}					В
			ZM////2/7/8	.E513913														_
A										JYA®								
									www.ł	Panyu Dist. Guangzhou 511495.								
							TITLEWIRE CONNECTORS AND SOLDERINGALUGS FOR CODE AND FLEX CABLEA											
	00	23-Aug-25	Ruby Feng	Sinia Qiu	Cel		ards Spec. Initialed.		WR	OUGHT COPPER		34P-251		CALE N	rs ^{thr}			
1	REV	DATE	DWN	СНК	1	DESCR		ECN		CTRO TIN PLATE	^{G. NO.} 1	86-cp20	69 U	init IN	CH +	Ψt		
			4				3	4		2					1			