	-				I									
		4		3	\downarrow	:	2		1		1			
ı			HE PROERTY OF CELESTRA,	IS	CELESTI	RA WI	RE SIZE	BOLT	' В	С	D	G	Н	l '
		NFIDENCE AND NOT TO T FOR WHICH FURNISHE	BE REPRODUCED, USED OR D.		CAT.NO		FLEX	SIZE	MIN	±0.04	±0.015	±0.02	±0.01	
					DB141058F	-250 14-10 AWG	-	#10	1.17	0.38	0.06	0.63	0.13	
_														l _
D	NOTE	4 411 514510	010 405 11 110150 1101											D
	NOTE:	1. ALL DIMENS	ONS ARE IN INCHES UNI	LESS OTHERWISE										
		2 ALL DA DRI	A LD W/D AND LCEDIEC (NE CAT NO S ARE	NDE									
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE BOLT SIZE													
		ON CODE WI	RES AND FLEX/24 STRAI											
		PRE-FIX CAT	.NO.WITH "L" HAS NOT P		- C - C									
	OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO.													
		WITH "P".			G									
	MATERIAL:	HIGH CONDU	ICTIVITY WROUGHT COF	PPER			P	4						
С	FINISH:		N PLATE UNLESS OTHER											С
Ū			_ATE PER MIL - T -16366. NO.WITH "SP" FOR SILVE		Color coded barrel markings									
		OOI TIX OAT.	NO.WITH OF FOR OILVE	_IX.			/			9-				
					<u>ر</u> ې/		Wire in	spectio	n hole)				
	Wire inspection hole B D													
\rightarrow	INSTALLATION GUIDE													\leftarrow
,	DIE CODE = DIE COLOR :				<u> </u>					1				
						Beve	eled wire entry							
						5010	nou vino ona y				Ц			
			,											
В		~(Ui)"	_ V											В
			ROHS 2002/95/EC											
		LISTED												
		WIRE CONNECTORS ZMVV/2/7/8.E513913												
_	1													_
							- A - C	ELES	TDA				201	
						HUY								
						www.huyac		76. Hua Panyu [11.	
Α														Α
^						TITLE WIRE	CONNECT	ORS.	AND) SO	LDER	RING		^
						LUGS	FOR CODI	EAND) FL	EX C	CABLI	E		
	00 23-Aug-25	Ruby Feng Sinia Q	Colostro St	andards Spec. Initialed.		MATERIAL HIGH-COND	UCTIVITY PRT. NO.	0505.55	S	CALE		ID ANGLE PE	ROJECTION	
					FON	WROUGHT O	DWG NO	058F-250		INIIT	TS +	⊕ €	7	
1	REV DATE	DWN CHK) DES	SCRIPTION	ECN	ELECTRO TIN	I PLATE	186-cp21	03	IN.	ICH	\$ L	7	
	_	4		3	4	2					1			
					I									