			4					3	$\bigvee$			2					1		_
'						OF CELESTRA,				CELESTR CAT.NO		Wire Range	STUD SIZI	A MAX	B ±0.003	C C	D ±0.002	H ±0.010	'
			FOR WHICH							TR2238		AWG 22 - 16	3/8	1.004			0.039 (1.00)		
D	N	OTE:		DIMENSION CIFIED.	IS ARE II	N INCHES UN	ILESS OT	HERWISE	·		-								D
	<ol> <li>ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.</li> </ol>									BRAZED SEAM SERRATED BARREL BEVELED EPGE									
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".									$\Big) \Big) $	 							
С		IATERIAL: INISH:	ELE SPE	CTOR-TIN P CIFED PLAT	LATE UN TE PER M	ROUGHT CO NLESS OTHER MIL - T -16366 SP" FOR SILVI	RWISE								<i>y</i>			y	С
			001	TIX OXTVO										<b>—</b> A—					
-	D	NSTALLATION NE CODE = NO NE SILE COLOR =										  -  -			·		D		
В			U	RoH 2002/95/6	, S								·		•	İ	1		В
_			TERED PR																
											JYA uyaco.con	7	6. Huan	cun Ro	l. Zhor	PORATI agcun Tow u 511495	٧n.		
Α											LUGS FOR CODE AND FLEX CABLE								А
	00	05-Dec-25	Ruby Feng							MATERIAL HIGH-CONDUCTIBITY PRT. NO. WROUGHT COPPER TR2238				SCALE NTS THRID ANGLE PROJECTION					
1	REV	DATE	DWN	CHK		DES	SCRIPTI			ECN FIN		TRO TIN PLATE	DWG. NO.	6-cp2150	UNIT	INCH	1 🕀 1		
			4				3				4	2					1		