		4			3	\downarrow		2					1		
'				DERTY OF CELESTRA RODUCED, USED OR			CELESTRA	Wire Range	STUD SIZE	A	В	С	D	Н	· '
	DISLOSED EXCEPT			NODOCED, OSED ON			CAT.NO	AWG 8			±0.003			±0.010	ł
							TR0885	8	5/18	1.969	0.677	1.26	0.047 (1.20)	0.177	
D															D
	NOTE:			ARE IN INCHES UN	ILESS OTHERWISE										
		SPECI					DDAZ	ED CEAM					/ -B		
					OF CAT.NO.S ARE ND "CSA" FOR USE		SERRATED	ED SEAM—				_		á.	
				ND FLEX/24 STRA				ED EPGE				/	\wedge		
	1	PRE-F	IX CAT.NO.V	/ITH "L" HAS NOT	PEEP HOLE UNLESS		2212					\nearrow	\ \		
				IFIED IN THE SUF	FIX OF THE CAT.NO.			i IT			<u> </u>		→ / d	·	
		WITH "	"P".									/ <u> </u>	/ / I		
	MATERIAL:	HIGH (CONDUCTIV	TY WROUGHT CO	PPER						\rightarrow		´ /		
С	FINISH:			TE UNLESS OTHE PER MIL - T -16366									/	,	С
				ITH "SP" FOR SILV											
								V		—A—					
	INSTALLATIO	ON GUIDE													1
	DIE CODE =							<u></u>					_		
	DIE COLOR :	=						li					P		
								<u> </u>	<u> </u>		-		<u> </u>		
												I	1		
В				V											В
		# Ur		RoHS											
		E 8 L	Ø												
		CERED	•												
								11137 A	® CE	LES	ΓRA (CORF	PORATION	ON	
								AYUh	76	. Huan	cun Ro	d. Zhor	ngcun Tow	'n.	
							W	ww.huyaco.con	n Pa	nyu Di	st. Gua	angzho	ou 511495.		
Α							TITLE	WIRE CON	INECTO	RS A	.ND :	SOL F	DERING		Α
								LUGS FOF							
								RIAL HIGH-CONDUCTIBITY		/ (IND	SCAL		THRID ANGLE P	DO IECTION	
		, ,	Sinia Qiu		tandards Spec. Initiale	d.		WROUGHT COPPER	TR08			NTS		LOSECTION	
1	REV DATE	DWN	CHK	DE:	SCRIPTION	A	ECN FINISH	ELECTRO TIN PLATE	DWG. NO. 186	6-cp2187	UNIT	INCH	1 4 1		
		4			3	4		2					1		
	-					1									