			4		I		3	\downarrow		2		I			1		
1	DISCL	OSED IN CON) NOT TO BE F	PROERTY OF CI REPRODUCED, U			•	CELESTR/ CAT.NO	A Wire Range AWG	STUD SIZE	A MAX	В ±0.003	C ±0.008	D ±0.002	H ±0.010	
	0.020								TR1014	1/0	1/4	1.929	0.26	0.866	0.075 (1.90)	0.449	
D																	D
D	N	IOTE:		DIMENSION CIFIED.	IS ARE IN INCHES UNLESS	OTHERWISE								_		D	
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE SERRATED																
			ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS								\frown						
			OTH				HOLE UNLESS F THE CAT.NO.			H		/	-		\rightarrow) .		
		IATERIAL:	_									1					
С	F	INISH:	SPE	CIFED PLAT	LATE UNLESS TE PER MIL - 1 WITH "SP" FO	-16366.	E									y Y	С
										~		—A—					
INSTALLATION GUIDE DIE CODE = DIE COLOR =													\leftarrow				
	D																
В					\mathbf{V}												В
			EL ®		2002/95/EC	ľ											
			STER!	DA													
																	—
A										HUYA	\sim						
									icun Rd. Zhongcun Town. st. Guangzhou 511495.				_				
											VIRE CONNECTORS AND SOLDERING UGS FOR CODE AND FLEX CABLE						A
		23-Aug-25	Ruby Feng	Sinia Oiu	C_	lestra Standa	rds Spec. Initialed.		MAT	MATERIAL HIGH-CONDUCTIBITY PRT. NO.			SCALE THRID ANGLE PROJECTION				
1	REV		DWN	CHK		DESCR			ECN FINIS	WROUGHT COPPER SH ELECTRO TIN PLATE	DWO NO)14 6-cp2227	, UNIT	NTS INCH	- • {	\square	
		-	4				3	4		2					1		