			4				3		7	2					1			
I	DISCL	OSED IN CON		D NOT TO BE I	PROERTY OF CE REPRODUCED, U				ELESTRA CAT.NO 0238P-261	WIRE CODE 2 AWG	SIZE FLEX 150/24 #2 We	BOLT SIZE d 3/8	A ±0.06 2.46	B MIN 0.83	C ±0.04 0.68	R 1.63	ID ±0.01 0.36	
D	N	 NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE 							Color coded marking Bolt Size									
	2. ALL DA, DB, LA, LB, WF AND 3 SINLES OF CALINO.S AND LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".																	
С		IATERIAL: INISH:	HIGI ELE SPE	H CONDUCT CTOR-TIN P CIFED PLAT	TIVITY WROUG LATE UNLESS TE PER MIL - T WITH "SP" FC	OTHERWIS -16366.					A B							С
\rightarrow	D	INSTALLATION GUIDE DIE CODE = 33 DIE COLOR = Brown							P Inspection Hole									
В	COUS ANEBS ³ ESCE														В			
		WIRE CONN	ECTOR															_
А												76. Hua	ELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.					
										TITLE WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE								A
	00 Rev	23-Aug-25 DATE	Ruby Feng	Sinia Qiu CHK	Cel	lestra Standa	ards Spec. Initiale	d.	ECN	MATERIAL HIGH-CONDUC WROUGHT CO	DPPER LA	0238P-261 186-cp02	_	NIT	rs -	ID ANGLE PF		
			4			DESCR	3	4		ELECTRO TIN F	LAIE	100-0002	.20	IN	сн 1	+ -	7	J