			4				3	\downarrow		2					1		
1	DISCL	OSED IN CON		D NOT TO BE F	PROERTY OF CE REPRODUCED, U			*	CELESTRA CAT.NO	Wire Range	STUD SIZE	A MAX	B ±0.003	C ±0.008	D ±0.002	H ±0.010	
	DIOLO							ĺ	TR1610VM	1 16 - 14	#10	0.906	0.209	0.335	0.031 (0.80))	
D																	D
U	N	IOTE:		DIMENSION CIFIED.	IS ARE IN INCHES UNLESS	OTHERWISE										U	
		 ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE 							BRAZED SEAM								
					S AND FLEX/24												
			OTH				HOLE UNLESS F THE CAT.NO.			ų 🗍		7	-		$\left. \right)$		
		IATERIAL:			IVITY WROUG							۲	$\langle \rangle$				
С	F	INISH:	SPE	CIFED PLAT	LATE UNLESS TE PER MIL - T .WITH "SP" FO	-16366.	E									2 2	С
2												—A—					4
INSTALLATION GUIDE DIE CODE = DIE COLOR =														\leftarrow			
													1				
В					\mathbf{V}												В
					ROHS 2002/95/EC												
			STER	DAY													
А										ΗυγΑ	\sim						
								TOTA76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.									
									TITLI	WIRE CONNECTORS AND SOLDERING A							
		00 Aug 05	Duby Farra	Cinia Oiu	0-1		rdo Copo Jatista d		LUGS FOR CODE AND FLEX CA						THRID ANGLE F	PROJECTION	
	REV		Ruby Feng	CHK	Cel	DESCR	rds Spec. Initialed.		ECN FINIS	WROUGHT COPPER	TR161	0VM 6-cp2354	1 UNIT	NTS INCH	\neg	\square	
			4	. I			3	4		2	1				1		