	,	_		ı	_	<u></u>	_								$\overline{}$	
		4		<u> </u>	3	V	2 WIRE SIZE		1 1	<u> </u>		1		I	,	
	DISCLOSED IN COI	NFIDENCE AND N	IOT TO BE REPRO	RTY OF CELESTRA, IS DUCED, USED OR		CELESTRA CAT.NO	CODE	FLEX	BOLT   SIZE	A ±0.06	B MIN	C ±0.04	R	ID ±0.01		
D	DISLOSED EXCEP	T FOR WHICH FUI	RNISHED.			DA0138-260	1 AWG	75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223	3/8	1.96	0.83	0.68	1.13	0.36	D	
	NOTE:	1. ALL DII SPECII		E IN INCHES UNLE	SS OTHERWISE											
		2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.  Color coded marking Bolt Size														
	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".  MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER															
	MATERIAL:	HIGH C	CONDUCTIVITY	WROUGHT COPP	ER											
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.  B  A										С					
$\rightarrow$	DIE CODE =	INSTALLATION GUIDE DIE CODE = 37 DIE COLOR = Green													$\leftarrow$	
В	c (	Dus 🚼	NEB	s3 Ross	(€		R	Inspection	on Hole	e	E				В	
	WIR	E CONNECTOR					Beveled	a entry								
	1														_	
А				_			HUY www.huyaco	A	<b>ELES</b> '6. Hua Panyu D	ncun l	Rd. Zh	nongcl	ın Tow	_		
						WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
	00 01-Dec-25	Ruby Feng S	Sinia Qiu	Celestra Stan	dards Spec. Initialed.		MATERIAL HIGH-CONDUC WROUGHT CO	CTIVITY PRT. NO. DPPER DA01	38-260	SC	CALE N7		RID ANGLE PI	ROJECTION		
ı	REV DATE	DWN	CHK	DESC	RIPTION	ECN	FINISH ELECTRO TIN F	PLATE DWG. NO. 1	86-cp023	37 Ut	NIT IN	СН	<b>⊕</b> €	$\exists$	,	
		4			3	$\uparrow$	2					1				