		4		3	\bigvee		2					1		
'			THE PROERTY OF CELESTR. BE REPRODUCED, USED OF			CELESTRA CAT.NO	Wire Range	STUD SIZE	A MAX	B ±0.003	C .000	D . 0.003	H	'
		T FOR WHICH FURNISH				TR1604NM	AWG 16 - 14	#4	0.811	0.126		±0.002 0.031 (0.80)	±0.010	
					_				0.0	01120	0.20	<u> </u>		
D	NOTE:	4 ALL DIMEN	NONC ADE IN INCLIES L	NI ECC OTHEDWICE										D
	NOTE:	SPECIFIED	SIONS ARE IN INCHES U	NLESS OTHERWISE								_		
		2. ALL DA,DB,		BRAZE	D SEAM—					/B				
			'UNDERWRITERS INC." / /IRES AND FLEX/24 STR			SERRATED E	\ \						í	
	1					BEVELE	D EPGE \				1	. \		_
			T.NO.WITH "L" HAS NOT E SPECIFIED IN THE SUI) <u> </u>		
		WITH "P".					H				7	ナルタ	,	
	MATERIAL:	HIGH CONE	UCTIVITY WROUGHT CO	OPPER						\rightarrow	\Box	′ /		
С	FINISH:		IN PLATE UNLESS OTHE PLATE PER MIL - T -1636									/	,	С
			NO.WITH "SP" FOR SIL											
							<u> </u>		—A—			ightharpoonup		
\rightarrow	INSTALLATIO													4
	DIE CODE =											D		7
		_									I	Ţ		
										-		1		
В			./									,		В
D			.RoHS											J
		图 & L 月	2002/95/EC											
		THE DESIGNATION OF THE PERSON												
	1													_
								® CE	LEST	RA C	ORP	ORATI	ON	
							UYA					gcun Tow		
_				_		ww	w.huyaco.com	n Pai	nyu Dis	st. Gua	ingzho	u 511495.		
Α							WIRE CONNECTORS AND SOLDERING A							
	LUGS FO						LUGS FOR	R CODE AND FLEX CABLE						
	00 23-Aug-25	Ruby Feng Sinia	tuby Feng Sinia Qiu Celestra Standards Spec. Initialed.				HIGH-CONDUCTIBITY WROUGHT COPPER	PRT. NO. TR1604	1NM	SCAL	E NTS	THRID ANGLE P	ROJECTION	
	REV DATE	DWN CH		SCRIPTION		ECN FINISH			-cp2380	UNIT	INCH	 	\exists	
		4		3		ı	2		•	 	,0,,	1		
			ı		T					I				