			4				3	\downarrow		2					1			
I	DISCL	OSED IN CON	FIDENCE AND	D NOT TO BE I	PROERTY OF C REPRODUCED,	CELESTRA, IS USED OR		CELESTRA CAT.NO	W CODE	RE SIZE	BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.				DB061012	#6 AWG	#6 Weld 61/24 = 24.6 kcmil	#10	1.98	1.28	0.44	0.08	0.50	0.26	
											I							
D	N	IOTE:	1. ALL SPE									D						
			LIST	ED BY "UND	DERWRITERS	SERIES OF C. S INC." AND "(/24 STRANDE	CSA" FOR USE	Color coded barrel markings										
			OTH		D.WITH "L" HA PECIFIED IN T													
		IATERIAL:				IGHT COPPER			Die				- 					
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С					
\rightarrow	INSTALLATION GUIDE DIE CODE = 24								1-822227	-Wire ins	pectio	n hole			4			\triangleleft
		NE COLOR :							₩ *		B		1					
В			₀€	Dus	RoHS	S			\B€	eveled wire entr	у	[J					В
						•												
																		—
										JYA® nuyaco.com	7	ELES '6. Hua Panyu [ncun	Rd. Zh	iongcu	in Tow		
A								WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									А	
		23-Aug-25			C		rds Spec. Initialed.		WR	OUGHT COPPER		61012		CALE N			OJECTION	
	REV	DATE	DWN	СНК	1	DESCR		ECN			^{G. NO.} 1	86-cp24	93	IN	сн 1 1	Ψt		
			4				3	4		2			I		I			