	-		4		ı		0	,	+		0			ĺ		4			
	THE II	NFORMATION	ON THIS DRA	WING IS THE	PROERTY C	F CELESTRA, IS	3		2 ELESTRA WIRE SIZE		BOLT	Α	В	С	1	G	Н	i	
	DISCL	LOSED IN CON	NFIDENCE AND	NOT TO BE					CAT.NO	CODE	FLEX	SIZE	±0.06	MIN	±0.04	1	±0.02	±0.01	
								DB	061058-260	#6 AWG	#6 Weld 61/24 = 24.6 kcmil	#10	2.16	1.15	0.42	0.09	0.63	0.26	
												•	•		•	•	•	,	
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.															D			
			LIST	ED BY "UNI	DERWRITE	J SERIES OF ERS INC." AND EX/24 STRAND		Color coded barrel markings  BOLT SIZE											
			OTH				EP HOLE UNLES: ( OF THE CAT.NC		DOE! OIZE										
	N	MATERIAL:	HIGH	H CONDUCT	TIVITY WR	OUGHT COPP	ER												
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С						
		NSTALLATIO DIE CODE = DIE COLOR =	24					Wire inspection hole  H  B  H  A  B  A  B  B  B  B  B  B  B  B  B  B											
В			C U		Rol- 2002/98	IS Æ				Ве	eveled wire entr	у	ſ	Ď					В
_			ZMVV/2/7/8	E513913															
											JYA® nuyaco.com	7	'6. Hua	ancun	Rd. Zh	nongci	RATION Un Tow 11495.	_	
Α								WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE											
00 01-Jul-25 Ruby Feng Sinia Q					Celestra Standards Spec. Initialed.			led.		MATERIAL HIGH-CONDUCTIVITY PRT. NO. WROUGHT COPPER DB061058-260 NTS THRID ANGLE PROJECTION									
ı	REV	DATE	DWN	СНК		DESC	RIPTION		ECN	FINISH		0.110	86-cp25		NIT	CH -	<b>(</b> ) E	<u></u>	
			4				3		$\uparrow$		2					1			