																$\overline{}$
		4			3	$\overline{V}$	2					1	1			,
	DISCLOSED IN CO	N ON THIS DRAWING INFIDENCE AND NOT	TO BE REPROD			CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
	DISLOSED EXCER	T FOR WHICH FURNI	SHED.			DB061058-261	#6 AWG	#6 Weld 61/24 =	#10	1.85	1.15	0.44	0.07	0.63	0.27	
						DB001030-201	#0 / 1/10	24.6 kcmil	#10	1.00	1.15	0.44	0.07	0.03	0.27	
<b>D</b>																_
D	NOTE:	1. ALL DIME	NSIONS ARE	IN INCHES UNLES	SS OTHERWISE											D
	SPECIFIED.															
				L,AS AND J SERIE	S OF CAT.NO.S ARE	Color coded barrel markings										
		/-Color coded barrer markings														
			PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS													
		OTHERW WITH "P".		D IN THE SUFFIX	OF THE CAT.NO.											
	MATERIAL:			WROUGHT COPPE	-R			) <u>\$</u>								
0	FINISH:			JNLESS OTHERWI										С		
С	1 11 11 11 11	SPECIFEI	D PLATE PER		G-G											
		SUFFIX C	AT.NO.WITH	"SP" FOR SILVER.			<b>—</b>	A								
_	INSTALLAT	INSTALLATION GUIDE						-Wire inspection hole								
	DIE CODE =		H B B													
	DIE COLOR	= blue				l				_	<u>-</u>	_	Ψ,			
							<b>\</b>		Ī		Ī		<del>'   '</del>			
В							\Ве	eveled wire entr	у		)					В
Ь		(h)	<b>V</b>													
	"	US I	ROHS P002/95/EC													
	,	LISTED WRE CONNECTORS ZMVV/2/7/8.E513913														
									,							
									C	ELES						
A						HUYA® CELESTRA CORPORATI 76. Huancun Rd. Zhongcun Tow www.huyaco.com Panyu Dist. Guangzhou 511495								n.		
															A	
					Wike Connectors and Soldering											
							LUGS FOR CODE AND FLEX CAB									1
	00 01-Dec-25 Ruby Feng Sinia Qiu Celestra Standards Sp				lards Spec. Initialed.	WROUGHT COPPER   DB061058-261   NTS							RID ANGLE PE	ROJECTION		
1	REV DATE	DWN C	HK	DESC	RIPTION	ECN		CTRO TIN PLATE	9. NO. <b>1</b>	86-cp252	28 U	nit IN	СН -	<b>⊕</b> €		1 ,
		4			3	$\triangle$		2					1			
						I										