									1													
		4						3	\forall		2			1								
·		THE INFORMATION ON THIS DRAWING IS THE PROE DISCLOSED IN CONFIDENCE AND NOT TO BE REPRO						CE	CELESTRA	WIRE SIZE		BOLT	A	В	С	_	ID	1				
			FIDENCE ANI		REPRODUC	CED, USED OR			CAT.NO	CO	DE	FLEX	SIZE	±0.06	MIN	±0.04	R	±0.01				
D	DISLUSI	LD EXCEPT							LA0156	1 A\	WG kc	Navy #2 Weld i0/24 = 60.5 mil 175/24 = 70.6 kcmil 133/.0223	5/16	2.01	0.88	0.68	1.13	0.36	D			
	NO	DTE:		DIMENSION CIFIED.	IS ARE IN	I INCHES UN	ILESS OTH	HERWISE	L													
			LIST	ED BY "UND	DÉRWRIT	D J SERIES (ERS INC." AI .EX/24 STRA	Color coded marking Bolt Size															
			OTH			-" HAS NOT F IN THE SUFF																
	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER 별										H H H H H H H H H H H H H H H H H H H											
С													С									
\rightarrow	DIE	STALLATIC E CODE = 3 E COLOR =	37								5	Inspectio	on Hol	0					\triangleleft			
В			ם בי	. N	IEB	S 3	RoHS	CE							E				В			
		WIRE CONN	IECTOR								Beveled en	try										
																			-			
۸										H	UY	\sim										
									- <u>ww</u> w.	www.huyaco.com Panyu Dist. Guangzhou 5114					11495.							
А										ITTLE WIRE CONNECTORS AND SOLDERING A LUGS FOR CODE AND FLEX CABLE A												
	00 23-Aug-25 Ruby Feng Sinia Qiu					Celestra Standards Spec. Initialed.				MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PR WROUGHT COPPER LA0156 NTS					ROJECTION	CTION						
		DATE	DWN	СНК			SCRIPTI	-	ECN	FINISH	ECTRO TIN PLATE	DWG NO	86-cp02	55 ^{UI}	NIT	СН	(E	\square				
		4 3						4		2					1							
									I													