			4		1		2	+	2			ı		1			\neg
	THEIN	JEODMATION	4 I ON THIS DR	AWING IS THE	DDOEDTY (OF CELESTRA, IS	3	OFI FOTDA	2 WIRE SIZE		DOLT.	<u> </u>		I		ID.	ı
	DISCL	OSED IN CON	VFIDENCE AN	D NOT TO BE				CELESTRA CAT.NO	CODE	FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	R	ID ±0.01	
D	DISLO	SED EXCEPT	FOR WHICE	FURNISHED.				LA0156	1 AWG	75 Navy #2 Weld 150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/.0223	5/16	2.01	0.88	0.68	1.13	0.36	D
	N	OTE:	ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.														
			LIS	2. ALL DA,DB,LA,LB,WP,AL,AS AND J SERIES OF CAT.NO.S ARE LISTED BY WINDER AND STEEN OF CAT.NO.S ARE LISTED BY WINDER BY WINDER AND STEEN OF CAT.NO.S ARE LISTED BY WINDER													
_			ON	ON CODE WIRES AND FLEX/24 STRANDED CABLES. Bolt Size										_			
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". ATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER															
	М	IATERIAL:	HIG	H CONDUC	TIVITY WR	OUGHT COPPER	₹		DIE C	3							
С	F	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER. B A											С				
								-	-		-						
	D	ISTALLATION IE CODE = 1 IE COLOR =	37														\leftarrow
В		c (LIS	D us STED CONNECTOR	≧ N	EBS	3 ROHS	∶ €		R	Inspecti	on Hole	8	6				В
	ł																
									HUY www.huyaco	A	ELES 76. Hua Panyu [incun	Rd. Zh	nongcu	ın Tow		
Α						_		TITLE WIRE CONNECTORS AND SOLDER							ING	A	
			LUGS FOR CODE AND FLEX CABLE														
	00	01-Dec-25	Ruby Feng	Sinia Qiu		Celestra Standa	rds Spec. Initialed.		MATERIAL HIGH-CONDUC WROUGHT CO	PPER PRT. NO.	0156	S	cale N		ID ANGLE PR	OJECTION	
ı	REV	DATE	DWN	CHK		DESCRI	PTION	ECN	FINISH ELECTRO TIN F	DWG. NO.	186-cp02	55 U	nit In	СН	⊕ £	\rightarrow	
			4				3	\uparrow	2					1			