	•				_			I												
			4				3	$\overline{}$		2					1					
'			I ON THIS DRA NFIDENCE ANI			CELESTRA, IS D, USED OR		CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	D +0.015	G ±0.02	H ±0.01			
	DISLO	SED EXCEPT	FOR WHICH	FURNISHED.						#6 Weld 61/24 =	#10									
								LB061034P-260	#6 AWG	24.6 kcmil	#10	2.59	1.27	0.42	0.09	0.75	0.26			
_																		_		
D	_N	IOTE:	1. ALL	DIMENSION	IS ARE IN II	NCHES UNLES	S OTHERWISE											D		
				CIFIED.																
						J SERIES OF C									markings					
		LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.							Color coded barrel markings BOLT SIZE											
		PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS																		
				IERWISE SF H "P".	PECIFIED IN	THE SUFFIX C	OF THE CAT.NO.													
	,	MATERIAL:				UGHT COPPE	D.													
		INISH:				SS OTHERWIS							<u>!</u>					_		
С	「	IINIOH.	SPE	CIFED PLAT	ΓE PER MIL	- T -16366.	DE .			_	G⊸∽							С		
			SUF	FIX CAT.NC).WITH "SP"	FOR SILVER.			V	——A——		_>								
_		NSTALLATIO					-Wire inspection hole									_				
	D	DIE CODE =	24						HB											
		DIE COLOR :	= Blue					ı	1				<u></u>		\forall					
									1						+++	<u> </u>				
_						,			\Ве	eveled wire entr	٧	[)							
В			c(N	L)us	.RoH	S.					,							В		
			1101	TEN .	2002/95/E	6														
			WIRE CONN ZMVV/2/7/8																	
										IV AR	С	ELES	TRA	COI	RPO	RATIO	NC			
										JYA®		'6. Hua					n.			
٨										nuyaco.com		Panyu E						,		
Α								WIRE CONNECTORS AND SOLDERING										A		
									LUGS FOR CODE AND FLEX CABLE											
	00	01-Jul-25	Ruby Feng	Sinia Qiu		Celestra Standa	ards Spec. Initialed.	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION WROUGHT COPPER LB061034P-260 NTS									ROJECTION			
1	REV	DATE	DWN	СНК		DESCR	IPTION	ECN	FINISH			86-cp25		NIIT	CH .	() E	\exists			
		-	4				3	Δ		2			İ		1					
	•				•			I					•							