			4				3	+		2					1			
I			I ON THIS DRA			OF CELESTRA, IS ED, USED OR		CELESTRA CAT.NO	WIRE SIZE		BOLT SIZE	A ±0.06	B MIN	C ±0.04	D +0.015	G ±0.02	H ±0.01	
			FOR WHICH					LB063878P-251	#6 AWG	#6 Weld 61/24 =	3/8	2.99	1.72	0.62	0.06	0.88	0.27	
										24.6 kcmil								
D																		D
	N	IOTE:		DIMENSION CIFIED.	IS ARE IN	INCHES UNLES												
					LA,LB,WP AND J SERIES OF CAT.NO.S ARE 'UNDERWRITERS INC." AND "CSA" FOR USE Color coded barrel markings —BOLT SIZE													
						EX/24 STRANDE		DOLI SIZL										
						" HAS NOT PEEF IN THE SUFFIX C												
			WITI	WITH "P".														
		MATERIAL:				COUGHT COPPE	G—G											
С		FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.							AC									
		/-Wire inspection hole																
								vviile inspection noie										
\rightarrow	INSTALLATION GUIDE DIE CODE = 24							H										
	D	DIE COLOR = Blue																
		Beveled wire entry																
В			(II))	_ \	/												В
			C	Jus	Rol 2002/9	IS 5/EC												
			LIST WIRE CONN ZMVV/2/7/8															
																		_
		I	I						I									
									H	JYA®		ELES '6. Hua						
	www.huyaco.cc									_								
А			TITLE WIRE CONNECTORS AND SOL															
								LUGS FOR CODE AND FLEX CABLE MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE THRID ANGLE PROJECTION										
		-	Ruby Feng				ards Spec. Initialed.	FON	WR	OUGHT COPPER	LB0638	378P-251	4	CALE N	TS _	RID ANGLE PF	ROJECTION	
	REV	DATE	DWN 4	CHK	I	DESCR	3	ECN_	ELEC	CTRO TIN PLATE	1	86-cp25	37 <u> </u>	IN	CH 1	Ψ -		
			r		I		3	4		_			I		•			