			4			3 2						1					
Ι	DISCL	OSED IN COM		D NOT TO BE	PROERTY OF CELES REPRODUCED, USED		CELESTRA CAT.NO	W CODE	IRE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
	DIOLO						DB041058-250	#4 AWG	40-50 Navy 91/24 = 36.7 kcmil 133/.0177 49/.029	#10	2.23	1.17	0.55	0.09	0.63	0.33	
D	N	OTE:		DIMENSION CIFIED.	NS ARE IN INCHES	UNLESS OTHERWISE											D
			2. ALL LIST	DA,DB,LA,L ED BY "UNI	DERWRITERS INC	ES OF CAT.NO.S ARE " AND "CSA" FOR USE "RANDED CABLES.	∠—Color coded barrel markings										
			PRE OTH	-FIX CAT.N	O.WITH "L" HAS NO	OT PEEP HOLE UNLESS UFFIX OF THE CAT.NO.											
0		ATERIAL:	HIGI	H CONDUC	TIVITY WROUGHT												
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.													С			
$\rightarrow$	INSTALLATION GUIDE DIE CODE = 29 DIE COLOR = Gray											$\left\langle -\right\rangle$					
В		Beveled wire entry													В		
		WIRE CONNECTORS ZMVV/2778.E513813															
A									JYA® nuyaco.com	7	6. Hua	incun	Rd. Zh		RATION In Tow		
								A TITLE WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE									
	00	23-Aug-25	Ruby Feng	Sinia Qiu	Celestr	a Standards Spec. Initialed.		MATERIAL HIGH-CONDUCTIVITY WROUGHT COPPER DB041058-250						rs 🛛			
	REV	DATE	DWN	СНК	[	DESCRIPTION	ECN		CTRO TIN PLATE	G. NO. <b>1</b>	86-cp25	99 U	NIT IN	СН 4	ΨL		1
			4			3	4		2			I		ľ			