	-																	
			4				3	$\nabla$		2			<u> </u>	,	1			.
	DISCL	LOSED IN CON	IFIDENCE ANI	O NOT TO BE F	PROERTY OF ( REPRODUCED,	CELESTRA, IS USED OR		CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	G ±0.02	H ±0.01	
	DISLC	OSED EXCEPT	FOR WHICH	FURNISHED.			J	DB041243-260	#4 AWG	40-50 Navy 91/24 = 36.7 kcmil 133/.0177 49/.029	1/2	3.89	2.83	0.83	0.12	1.75	0.30	
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.														D			
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES.  PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P".															_		
С	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER  FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												С					
	INSTALLATION GUIDE DIE CODE = 29 DIE COLOR = Gray  Wire inspection hole													$\leftarrow$				
В	Beveled wire entry  LISTED WIRE CONNECTORS ZMOV/207/8 E513813														В			
_	1																	_
								HUYA® Www.huyaco.com  CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.										
Α							WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE											
	00	23-Aug-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.					rds Spec. Initialed.	WROUGHT COPPER DB041243-260 NTS								ID ANGLE PR	OJECTION	
ı	REV	DATE	DWN	CHK		DESCRI		ECN		CTRO TIN PLATE	9. NO. <b>1</b>	86-cp260	1U 80	IN(	сн   (	(H)	$\Box$	
	-		4				3	$\triangle$		2					1			