	-	_		1	<u>_</u>	+		_			1					
	THE INFORMATION	A ON ON THIS DRAWI	ING IS THE PROF	RTY OF CELESTRA, IS	3	CELESTRA	١٨/	2 IRE SIZE	BOLT	Α	<u> </u> В	С	1	G	ш	, l
	DISCLOSED IN C	ONFIDENCE AND N PT FOR WHICH FU	NOT TO BE REPRO			CAT.NO	CODE	FLEX	SIZE	±0.06	MIN		±0.015	-	H ±0.01	
						WP041458-005	#4 AWG	40-50 Navy 91/24 = 36.7 kcmil 133/.0177 49/.029	?1/4	2.35	1.15	0.55	0.09	0.63	0.33	
D																D
	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.															
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. —Color coded barrel markings															
-	ON CODE WIRES AND FLEX/24 STRANDED CABLES. PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS Color coded barrel markings BOLT SIZE															
			RWISE SPECIF	TH "L" HAS NOT PEI IED IN THE SUFFIX	Huya C											
	MATERIAL	: HIGH (CONDUCTIVITY	WROUGHT COPP												
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												С			
\rightarrow		ΓΙΟΝ GUIDE						_Wire ins	pectio	n hole						4
В	DIE CODE DIE COLO			V		!	\$ \		B		<u>.</u>					В
Ь		LISTE WIRE CONNECT ZMVV/27/8 E512		ROHS 2002/95/EC			⊢B(eveled wire entr	у							
	1															
								JYA® nuyaco.com	7	ELES '6. Hua 'anyu [ncun	Rd. Zh	ongci	ın Tow		
Α					WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE											
	00 23-Aug-2	5 Ruby Feng S	Sinia Qiu Celestra Standards Spec. Initialed. MATERIAL HIGH-CONDUCTIVITY PRT. NO. WROUGHT COPPER WP041458-005 NTS								ID ANGLE PF	ROJECTION				
1	REV DATE	DWN	СНК	DESC	RIPTION	ECN	FINISH			86-cp26		NIIT	CH +	(E	\exists	
		4			3	\uparrow		2					1			