	-												1						
			4				3	V		2					1			,	
	DISCL	LOSED IN CON	NFIDENCE AND	O NOT TO BE F		CELESTRA, IS), USED OR		CELESTRA CAT.NO	CODE	IRE SIZE FLEX	BOLT SIZE	A ±0.06	B MIN	C ±0.04	D ±0.015	±0.02	H ±0.01		
	DISLC	JSED EXCEPT	FOR WHICH	FURNISHED.				LB041243-260	#4 AWG	40-50 Navy 91/24 = 36.7 kcmil 133/.0177 49/.029	1/2	4.20	2.83	0.81	0.12	1.75	0.30		
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.													D					
_	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. Color coded barrel markings BOLT SIZE														_				
		AATEDIAI -	PRE-FIX CAT.NO.WITH "L" HAS NOT PEEP HOLE UNLESS OTHERWISE SPECIFIED IN THE SUFFIX OF THE CAT.NO. WITH "P". HIGH CONDUCTIVITY WROUGHT COPPER																
С	"	MATERIAL: HIGH CONDUCTIVITY WROUGHT COPPER FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.											С						
	INSTALLATION GUIDE DIE CODE = 29 DIE COLOR = Gray									-Wire inspection hole									
В		LISTED ROHS													В				
_			WIRE CONN ZMVV/2/7/8															_	
							HUYA® Www.huyaco.com CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.												
А					_				WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE										
		04-May-25 Ruby Feng Sinia Qiu Celestra Standards Spec. Initialed.				WROUGHT COPPER LB041243-260 NTS								RID ANGLE PE	ROJECTION				
ı	REV	DATE	DWN	CHK		DESCF	RIPTION	ECN		CTRO TIN PLATE	9. NO. 1	86-cp264	14 U	nit IN	CH -	+ E		1 ,	
	-		4				3	\triangle		2					1				