	-	_	1	_	4		_			ı					$\overline{}$	
	THE INFORMATION	N ON THIS DRAWING	IS THE PROERTY OF CELESTRA	3	CELESTRA	2 WIRE SIZE		BOLT A		В	С	1 D	G	Lı	,	
	DISCLOSED IN C		TO BE REPRODUCED, USED OR		CAT.NO	CODE	FLEX	SIZE	±0.06	MIN	_	±0.015	-	H ±0.01		
					LB041243P-260	#4 AWG	40-50 Navy 91/24 = 36.7 kcmil 133/.0177 49/.029	?1/2	4.20	2.83	0.83	0.12	1.75	0.30		
D	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE SPECIFIED.														D	
	2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. Color coded barrel markings CBOLT SIZE												_			
		OTHERW WITH "P".														
С	MATERIAL FINISH:	ELECTOR	NDUCTIVITY WROUGHT CO											С		
	SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.															
	DIE CODE	INSTALLATION GUIDE DIE CODE = 29 DIE COLOR = Gray					-Wire inspection hole									
В	DIE GOLO	CUL) LISTED WIRE CONNECTORS ZMVV/2/7/8 E5/38/3	JS RoHS	ł	Beveled wire entry											
_	_														_	
				HUYA® Www.huyaco.com CELESTRA CORPORATION 76. Huancun Rd. Zhongcun Town. Panyu Dist. Guangzhou 511495.												
Α					WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE											
	00 23-Aug-2	5 Ruby Feng Sinia	a Qiu Celestra S	andards Spec. Initialed.	MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE WROUGHT COPPER LB041243P-260 N								ID ANGLE PF	ROJECTION		
ı	REV DATE	DWN C	:HK DES	SCRIPTION	ECN	FINISH ELEC	CTRO TIN PLATE	9. NO. 1	86-cp26	48 ^{UI}	nit IN:	СН	+ E	\rightarrow		
	-	4		3	\uparrow		2					1				