			ı			+		•			ı		4			
	THE INFORMATION	4 I ON THIS DRAWING	S IS THE PROER	Y OF CELESTRA, IS	3	CELESTRA	W	2 IRE SIZE	BOLT	Α	<u> </u> В	С		G	Н	ı
	DISCLOSED IN CON DISLOSED EXCEPT	NFIDENCE AND NO	T TO BE REPROD			CAT.NO	CODE	FLEX	SIZE	±0.06	MIN		±0.015	-	±0.01	
						LB041034P-260	#4 AWG	40-50 Navy 91/24 = 36.7 kcmil 133/.0177 49/.029	?#10	2.64	1.27	0.49	0.09	0.75	0.30	
D	NOTE:	NOTE: 1. ALL DIMENSIONS ARE IN INCHES UNLESS OTHERWISE														D
		SPECIFII														
		2. ALL DA,DB,LA,LB,WP AND J SERIES OF CAT.NO.S ARE LISTED BY "UNDERWRITERS INC." AND "CSA" FOR USE ON CODE WIRES AND FLEX/24 STRANDED CABLES. —Color coded barrel markings														
		OTHERW	ISE SPECIFIE	"L" HAS NOT PEE D IN THE SUFFIX	BOLT SIZE											
		WITH "P"														
	MATERIAL:			WROUGHT COPPE												
С	FINISH: ELECTOR-TIN PLATE UNLESS OTHERWISE SPECIFED PLATE PER MIL - T -16366. SUFFIX CAT.NO.WITH "SP" FOR SILVER.												С			
\rightarrow	. INSTALLATIO							/-Wire ins	pectio	n hole						\leftarrow
В	DIE CODE = DIE COLOR :		ŀ	H B D												
		C LISTED WIRE CONNECTOR: ZMVV/27/8 E513813	US R	0HS 02/95/EC			<u></u> Βε	eveled wire entr	у							В
								JYA® nuyaco.com	7	ELES 6. Hua anyu D	ncun	Rd. Zh	ongci	ın Tow		
Α				WIRE CONNECTORS AND SOLDERING LUGS FOR CODE AND FLEX CABLE												
	00 23-Aug-25	Ruby Feng Sin	ia Qiu	Celestra Stand	dards Spec. Initialed.	ed. MATERIAL HIGH-CONDUCTIVITY PRT. NO. SCALE WROUGHT COPPER LB041034P-260 NT								ID ANGLE PF	ROJECTION	
	REV DATE	 	CHK	DESC	RIPTION	ECN	FINISH			86-cp26		NIIT	CH	+ E		
		4	·		3	4		2					1			
						1										